




***Flatnet Mining  
Distribution Pipe  
For Copper  
, Nickel, Gold  
& Uranium Heap  
Leaching  
Irrigation.***



***Flatnet Pipe Is Highly Portable, Flexible  
And Lightweight Distribution Pipe***

# FlatNet™

## Reinforced Polyethylene Flexible Pipe

### *For Mining Heap leaching Irrigation systems.*


FlatNet™ Mining Pipes is a robust piping solution for mainline and sub-mainline drip and sprinkler applications. A high-performance and cost-efficient product, FlatNet features unique integral welded outlets that lower installation costs, while ensuring a secure, leakage-free connection between distribution pipes and laterals. Available in a wide range of diameters, FlatNet addresses the design requirements of any on surface or subsurface drip irrigation or sprinkler deployment.

A thermoplastic collapsible irrigation pipe constructed from premium polyethylene (PE), FlatNet offers many advantages over other pipe solutions. FlatNet is highly portable, flexible and lightweight, thereby reducing manpower, freight, maintenance and storage requirements. Versatile and durable, FlatNet is able to withstand the most stringent climatic and environmental conditions. A highly flexible solution, FlatNet completely eliminates buckling, making it ideal for high-pressure applications.

### **Specifications**

Compatible with ISO 16438 standard.

- Available diameters: 2", 3" and 4".
- Maximum working pressure 3.0 bar at 50 Celsius degrees.
- Coil length: 50, or 100 meter.
- Can be used as transportation blank pipe, as a distribution pipe with in-field stat connectors or as a distribution pipe with integral 1/2" female threaded connectors, distance between connectors must be defined at ordering time, according to the user needs.
- Robust and durable reinforced polyethylene weaves.
- White colored for high solar resistance,
- High chemical resistance and UV resistance.
- The pipe and the integral connectors are made of 100% Polyethylene, totally recyclable material.
- Red strip for easy identification.



*Integral 1/2"  
female threaded*





# Features & Benefits Flatnet™

## Technical Data

- 💧 Low expansion and zero axial elongation, no snaking.
- 💧 Flat and compact coil design,
- 💧 High chemical resistance.
- 💧 Reduces freight and storage and handling costs.
- 💧 confidence in the connections between distribution pipes and laterals,
- 💧 Light and flexible, easily moved from one installation to another.
- 💧 User friendly and faster layout and retrieving process, Lower maintenance requirements.
- 💧 Up to 80% lighter than other similar products.
- 💧 Complete package, pipes, full range of branching connectors and a complete line of connectors for dripperlines and laterals.
- 💧 Easier to work with on the pad , Saves labor on the pad.
- 💧 Conforms to odd shapes and layouts .
- 💧 Rolls lay out manually or by machine and can be retrieved with mechanized equipment
- 💧 No drilling and tapping required for lateral connections
- 💧 No glued PVC couplings or heat fusion welding of HDPE required.
- 💧 Only 2 sockets needed to install and retrieve.
- 💧 Durable factory installed, pre-spaced 1/2" deep FIPT outlets
- 💧 Eliminates fitting pop-outs common with other products
- 💧 Reduces labor with quality threaded connections that can be used over and over
- 💧 Enhanced composite fabric structure significantly reduces buckling and expansion (low expansion coefficient) typically seen with lay flat and other HDPE pipes
- 💧 Reinforced polyethylene weaves increase durability in rocky conditions.



### FLATNET™ Technical Data

| FLATNET™    | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) AT 50 DEGREES CELSIUS |
|-------------|----------------------|---------------------|-----------------------|---|
| 2" – 51 mm. | 51.5                 | 1.1                 | 53.7                  | 3.0   |
| 3" - 78 mm  | 78.3                 | 1.1                 | 90.5                  | 3.0   |
| 4" - 102 mm | 102.5                | 1.1                 | 104.7                 | 3.0   |

# FlatNet™ & Connector

## FLATNET™ Package Data



| FLATNET™    | Coil Length<br>100 m | Dimensions<br>Width<br>Diameter<br>(CM*CM) | Coil Weight<br>(KG) | Coil Per<br>Pallet<br>(Units) | Coil Length<br>50 m | Dimensions<br>Width<br>Diameter<br>(Cm x Cm) | Coil Weight<br>(Kg) | Coil Per<br>Pallet<br>(Units) |
|-------------|----------------------|--|---------------------|-------------------------------|---------------------|--|---------------------|-------------------------------|
| 2" - 51 mm. | 100                  | 9.0x78                                     | 16.5                | 22                            | 50                  | 9.0x57                                       | 9                   | 36                            |
| 3" - 78 mm  | 100                  | 14.0x78                                    | 29.5                | 14                            | 50                  | 14.0x57                                      | 15                  | 28                            |
| 4" - 102 mm | 100                  | 18.5x78                                    | 37.5                | 12                            | 50                  | 18.5x57                                      | 19                  | 24                            |

| Catalog Number                               | Product Description   | Product Picture |
|--|---|-----------------|
| 43040-000120<br>43040-000121                 | Fxn Barb Con Mth 2"x Bsp2" Kit W/O Clamp<br>Fxn Barb Con Mth 3"x Bsp3" Kit W/O Clamp      |                 |
| 43040-000100<br>43040-000101                 | Fxn Coupling Barb Con 2"x2" Kit W/O Clamp<br>Fxn Coupling Barb Con 3"x3" Kit W/O Clamp    |                 |
| 43040-000200<br>43040-000210                 | Fxn SSst316 Hose Clamp For Barb Conn 2"<br>Fxn Sst316 Hose Clamp For Barb Conn 3"         |                 |
| 77400-016400<br>77400-016600                 | Fxn 90 Deg Threaded Bsp Elbow 2" kit<br>Fxn 90 Deg Threaded Bsp Elbow 3" kit              |                 |
| 77400-014000<br>77400-014200                 | Fxn 90 Deg Threaded Bsp Tee 2" kit<br>Fxn 90 Deg Threaded Bsp Tee 3" kit                  |                 |
| 77400-011100<br>77400-011393                 | Fxn Thread Bushing Bsp 3"m x 2"f<br>Fxn Thread Bushing Bsp 2"m x 3"f                      |                 |
| 77400-021000<br>77400-021100                 | Fxn Pvc Threaded Cap 2"<br>Fxn Pvc Threaded Cap 3"  |                 |
| 77400-018250<br>77400-018000<br>77400-018200 | Fxn Pvc Nippel Reduce 3x2<br>Fxn Pvc Double Nippel Pvc 2"<br>Fxn Pvc Double Nippel Pvc 3" |                 |
| 1V30163000H                                  | Fxn Manual Flushing Valve -2"-FF  |                 |
| 1V30363000H                                  | Fxn Manual Valve 2" PVC F- M  |                 |
| 33010-009950<br>43040-006700                 | Fxn flange 110mmX3"Male Threaded<br>Fxn flange 90mmX3"Male Threaded<br>Assembled          |                 |
| 19900018                                     | Fxn PE Female Adaptor 63x2"   |                 |
| 43040-006200<br>43040-006230                 | O-ring Seal EPDM 40 x 4.5 For Barb Conn 2"<br>O-ring Seal EPDM 60 x 4.5 for Barb Conn 3"  |                 |



For More Information  
[dayan.m@aquaroyalspring.com](mailto:dayan.m@aquaroyalspring.com)  
[www.aquaroyalspring.com](http://www.aquaroyalspring.com)  
 Israel: +972-526960351  
 DRC : +243-824653780  
 Kazakhstan:+7 777-4480044